



Premium quality, super flexibility, softness and comfort. 13 gauge, special liner, cut level B, X-Wet PU

KEY FEATURES

- A premium quality cut level B glove with super flexibility, extra softness, comfort and a cool feeling when wearing in hand
- Thanks to special X-wet PU formulation, it offers a better grip performance than most other similar products in the market
- Great fitting and dexterity makes it ideal for general purpose works and also precision works



PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	13
Coating	Polyurethane
Finishing	Special X-wet
Colour	White / Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080

RECOMMENDED APPLICATIONS

General purpose, or works with low cut hazard in dry conditions.

Such as handling parts with sharp or rough edges, assembly, inspection, packaing, general handling...



CERTIFICATION


CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to Max. 5):	X
Tear (min.0 to max. 4):	4
Puncture (min.0 to max. 4):	3
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to Max. F, X - not tested):	B
Impact protection (P if pass, F if failed):	-

EN388:2016



4X43B

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-330W can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

